



The Foundry
of the Future
Since 1906

SUBMITTAL
ANACO COUPLINGS
Husky • Standard



Project

Architect

Engineer

Contractor

Date

**Meets
requirements of
Factory Mutual
1680.**

HUSKY

Heavy Duty Coupling

Coupling engineered to connect no-hub cast iron pipe in applications replacing the less-efficient hub & spigot material. Coupling consists of a patented neoprene gasket (ASTM C-564) housed inside a 304 stainless steel corrugated shield. Four or six (depending on size) 304 stainless steel clamps surround the shield and provide the sealing force. Screws are made from 305 stainless steel. HUSKY no-hub couplings are available in sizes ranging from 1-1/2" to 10". All HUSKY couplings are designed to be torqued to 80 in-lbs. Entire coupling is corrosion resistant. IAPMO Listed.



STANDARD COUPLINGS

Anaco standard couplings meet all requirements of the Cast Iron Soil Pipe Institute (CISPI 310) and state/local code standards. Neoprene gasket (ASTM C-564) surrounded by 301 stainless steel corrugated shield. Two stainless steel clamps provide the sealing force. IAPMO Listed.

Made in USA

7825 San Leandro Street • Oakland, CA 94621 • 800/GOT-IRON • 510/632-3467 • Fax 510/632-8035