



# Submittal Data

510030 - 08/141rev

Date \_\_\_\_\_

Project \_\_\_\_\_

Architect \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor \_\_\_\_\_

*Cast Iron No-Hub Pipe & Fittings*  
*Cast Iron SV Hub & Spigot Pipe & Fittings*  
*Anaco Standard Couplings*  
*Husky SD-4000 Heavy-Duty Couplings*  
*Husky HD-2000 Heavy Duty Couplings*  
*BestSet Closet Rings*  
*Ty-Seal and EZ-Tite Gaskets*




**No-Hub Pipe and Fittings** of 1-1/2" to 15" diameter. Soil waste, vent lines, rain water conductors and storm drainage lines shall be NSF Certified compliant and bear the registered trademark of the Cast Iron Soil Pipe Institute indicating that these items are manufactured to CISPI Standard 301, and ASTM 888. IAPMO File No. 3270.




**SV Hub & Spigot Pipe and Fittings** in sizes 2" to 15". Soil waste, vent lines, rain water conductors and storm drainage lines shall be NSF Certified compliant and bear the registered trademark of the Cast Iron Soil Pipe Institute indicating that these items comply with ASTM A-74 and HS-74.



**Anaco Standard Couplings** shall be NSF Certified compliant with the Cast Iron Soil Pipe Institute Standard 310, with shields, clamps and screw assemblies comprised of Series 300 stainless steel. Gaskets shall contain genuine neoprene as the primary elastomer and shall comply with ASTM C-564 and 1277, latest revisions, as manufactured by Anaco. Couplings shall bear the trademarks of NSF, and UPC or IAPMO.



**Husky SD-4000 Couplings** shall be constructed from 304 stainless steel and provide a minimum shield thickness of 0.015" or greater. Couplings shall have 4 sealing bands on sizes 1-1/2" - 4", and 6 sealing bands on 5" - 15" sizes. All bands shall require 80 in-lbs of torque. Gaskets shall contain genuine neoprene as the primary elastomer and shall comply with ASTM C-564. Couplings shall meet the requirements of Factory Mutual 1680 and ASTM 1540 standards. IAPMO Listed.



**Husky HD-2000 Couplings** shall be constructed from 304 stainless steel and provide a minimum shield thickness of 0.010" or greater. Couplings shall have 4 sealing bands on sizes 1-1/2" - 4", and 6 sealing bands on 5" - 10" sizes. All bands shall require 80 in-lbs of torque. Gaskets shall contain genuine neoprene as the primary elastomer and shall comply with ASTM C-564 and 1540. Couplings shall meet the requirements of Factory Mutual 1680. IAPMO Listed.



**BestSet Closet Rings** are cast iron rings developed and manufactured by AB&I. The BestSet features a gasket comprised of neoprene as the primary elastomer which fills the space around the pipe and space between the pipe and closet ring.



**Ty-Seal and EZ-Tite Gaskets** in sizes from 2" to 15" (Ty-Seal) and 2" - 6" (EZ-Tite) shall comply with all requirements of ASTM C-564. IAPMO File No. 0391.

**Sample Specs** 

AB&I is pleased to provide suggested wording for specifications to ensure that the DWV material specified truly meets the requirements of the various standards for cast iron pipe, fittings, and couplings. For details, contact your AB&I representative or call 800-468-4766.

